


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		RELEASED FOR PRODUCTION.	1/12/2016	RJC	JAG






NOTE:  
REFERENCE AGUSTA T/N 3G6305G05833.

<b>DART AEROSPACE</b>																							
TITLE TOOL KIT, T/R DRIVE QUILL RING NUT REM/INST																							
DWG NO. RBW6305G05833-3G	REV 1																						
<table border="1"> <tr> <td>MAT'L</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>HEAT TREAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH</td> <td>.XXX ± .005 FRACTIONS ± 1/8</td> </tr> <tr> <td></td> <td>.XX ± .01 ANGLES ± 5°</td> </tr> <tr> <td></td> <td>.X ± .1 SURFACES = 125/</td> </tr> <tr> <td>SPEC</td> <td>1. BREAK ALL SHARP EDGES</td> </tr> <tr> <td></td> <td>.015 x 45° OR .015R</td> </tr> <tr> <td></td> <td>2. DIMENSIONAL LIMITS APPLY</td> </tr> <tr> <td></td> <td>AFTER PLATING</td> </tr> <tr> <td></td> <td>3. INTERPRET DIM AND TOL PER</td> </tr> <tr> <td></td> <td>ASME Y14.5M-2009</td> </tr> </table>		MAT'L	UNLESS OTHERWISE SPECIFIED	HEAT TREAT	DIMENSIONS ARE IN INCHES	FINISH	.XXX ± .005 FRACTIONS ± 1/8		.XX ± .01 ANGLES ± 5°		.X ± .1 SURFACES = 125/	SPEC	1. BREAK ALL SHARP EDGES		.015 x 45° OR .015R		2. DIMENSIONAL LIMITS APPLY		AFTER PLATING		3. INTERPRET DIM AND TOL PER		ASME Y14.5M-2009
MAT'L	UNLESS OTHERWISE SPECIFIED																						
HEAT TREAT	DIMENSIONS ARE IN INCHES																						
FINISH	.XXX ± .005 FRACTIONS ± 1/8																						
	.XX ± .01 ANGLES ± 5°																						
	.X ± .1 SURFACES = 125/																						
SPEC	1. BREAK ALL SHARP EDGES																						
	.015 x 45° OR .015R																						
	2. DIMENSIONAL LIMITS APPLY																						
	AFTER PLATING																						
	3. INTERPRET DIM AND TOL PER																						
	ASME Y14.5M-2009																						
DRAWN BY: CLOUGH	USED ON MODEL																						
CHECKED: MACKOVJAK	AW139																						
OPPS APPR: ANDERSON																							
QA APPR: LINDSAY																							
APPROVED: GILBERT																							
SCALE 1:6	DATE 1/12/2016																						
SHEET 1 OF 4																							

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
				1	T/R DRIVE QUILL RING NUT REM/INST		RBW6305G10233-3G	1
				1	T/R DRIVE QUILL LOCKWASHER REMOVAL		RBW6305G10633-3G	1
		B/O	-1	1	BOTTOM FOAM	Y20, BLACK	3.95 X 9.08 X 11.98 (I.R. SPECIALTY)	2
		B/O	-3	1	TOP TOOL CUSHION	Y20, BLACK	1.20 X 9.08 X 11.98 (I.R. SPECIALTY)	3
			-5	1	PLACARD	PLASTIC	1/16 x 4 x 5	4
		B/O	-7	1	CASE	PLASTIC	PELICAN #APP-1400-E	N/S
		B/O		1	DART PLACARD	ALUMINUM	RB41011	N/S

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






①  
BOTTOM FOAM

<b>DART AEROSPACE</b>	
TITLE TOOL KIT, T/R DRIVE QUILL RING NUT REM/INST	
DWG NO. RBW6305G05833-3G-1	REV 1
MAT'L Y20, BLACK	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
HEAT TREAT	.XXX ± .010 FRACTIONS ± 1/8
FINISH	.XX ± .03 ANGLES ± 1°
SPEC	.X ± .1 SURFACES = 125
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: MACKOVJAK	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: GILBERT	AW139
SCALE 1:4	DATE 1/12/2016
SHEET 2 OF 4	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	




(-3)  
TOP TOOL CUSHION



<b>DART AEROSPACE</b>	
TITLE TOOL KIT, T/R DRIVE QUILL RING NUT REM/INST	
DWG NO. RBW6305G05833-3G-3	REV 1
MAT'L Y20, BLACK	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
.XXX ± .010 FRACTIONS ± 1/8	
.XX ± .03 ANGLES ± 1°	
.X ± .1 SURFACES = 125°	
SPEC	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: CLOUGH	
CHECKED: MACKOVJAK	
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
USED ON MODEL AW139	
SCALE 1:4	DATE 1/12/2016
SHEET 3 OF 4	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



ARIAL TEXT HT. 3/16



NOTE:  
USE DXF FOR MANUFACTURE.

(5)  
PLACARD

<b>DART</b> AEROSPACE	
TITLE TOOL KIT, T/R DRIVE QUILL RING NUT REM/INST	
DWG NO. RBW6305G05833-3G-5	REV 1
MAT'L PLASTIC	UNLESS OTHERWISE SPECIFIED
HEAT TREAT FINISH	DIMENSIONS ARE IN INCHES
SPEC	.XXX ± .010 FRACTIONS ± 1/8
DRAWN BY: CLOUGH	.XX ± .03 ANGLES ± 1°
CHECKED: MACKOVJAK	.X ± .1 SURFACES = 125°
OPPS APPR: ANDERSON	1. BREAK ALL SHARP EDGES
QA APPR: LINDSAY	.015 x 45° OR .015R
APPROVED: GILBERT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
SCALE 1:2	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 11/24/2015	USED ON MODEL
	AW139
	SHEET 4 OF 4